



Airfob Tag

Quick Guide

Version: 1.0.2 (English)




Product Size




Installing the Airfob Tag

1. Locate the card reader area on the digital door lock.



2. Remove the adhesive tape cover on the back of the Airfob Tag and attach the device over the card reader area.



Note

To replace the battery of Airfob Tag, remove and reinsert the battery, following the instructions on this page.



Replacing the Battery of Airfob Tag

If the Airfob Tag does not respond, **remove and reinsert or replace the battery.**

1. Lift the protrusion on the side of the body.
(*Use tools such as flat-blade screwdriver as it may cause injury when disassembling the product.)



2. Remove the top cover from the body of Airfob Patch.



3. Replace the coin battery (CR2032) inserted into the lower plate of the body. After replacement, tighten and assemble the top plate.
(*When assembling, press down with force to engage with a "click" sound.)



Note

Use CR2032 batteries. Battery operating times may vary by battery manufacturer.

Registering the Airfob Tag

Please refer to the airfob.com website.

If Digital Doorlock Does Not Respond

- For Airfob Tag to work, its RFID antenna must be aligned with the RFID antenna in the door lock. Try adjusting the position.
- Check if the remaining battery level of Airfob Patch is sufficient.
- Check the portal to ensure the Airfob Patch is registered.

FCC Compliance

THIS DEVICE COMPLIES WITH PART 15 OF THE FCC RULES. Operation is subject to the following two conditions:

1. This device may not cause harmful interference.
2. This device must accept any interference received, including interference that may cause undesired operation.

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures.

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Modifications not expressly approved by the manufacturer could void the user's authority to operate the equipment under FCC rules.